



Main

Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Plus
Number of gangs	2 gangs
Installation direction	Horizontal
Number of modules	2 x 6 modules
Fixing mode	Screws
Colour tint	White
Decoration colour	White

Complementary

Provided equipment	Fixing frame
Material	ASA + PC: cover frame ASA + PC: intermediate part LATER 4 G30V0 2307Y1 GRIS: fixing frame
Standards	EN 60669-1
Width	195 mm
Height	175 mm
Depth	16 mm
Distance between centers	69 mm
Net weight	0.18 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone

Liquid soap
 UV resistant
 Bleach
 Oil
 Window-cleaning fluid
 Ammonia
 Alcohol
 Petrol

Environmental health and issues	Halogen free
---------------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	172.33 g
Package 1 Height	2.1 cm
Package 1 width	17.6 cm
Package 1 Length	19.6 cm
Unit Type of Package 2	S02
Number of Units in Package 2	3
Package 2 Weight	949 g
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Weight	23.36 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------