



Main

| | |
|--------------------------------|---|
| Aesthetic name | Unica (standard aesthetic) |
| Product or component type | Rotary dimmer |
| Device presentation | Mechanism with zamak fixing frame |
| Fixing mode | Screws |
| Dimmer application | Motor Inductive load Resistive load |
| [Ue] rated operational voltage | 230 V AC 50 Hz |
| Number of modules | 2 modules |
| Cover plate colour tint | White |

Complementary

| | |
|------------------------------|--|
| Dimmer control | ON/OFF push |
| Maximum permanent current | 2.6 A |
| Total number of wires | 3 |
| Load type | 230 V AC halogen lamp - 40...1000 W 230 V AC incandescent lamp - 40...1000 W Low voltage halogen lamp with ferromagnetic transformer - 40...1000 VA 230 V AC motor - 60...600 W |
| Protection type | Current protection Electronic overvoltage protection |
| Marking | L+N |
| Connections - terminals | Screw terminals |
| Clamping connection capacity | <= 2 x 2.5 mm ² |
| Material | ASA + PC: mechanism cover Zamak: fixing frame |
| Standards | EN 60669-2-1 |
| Product certifications | CE AENOR |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | 5...30 °C |
| Ambient air temperature for storage | -20...60 °C |
| Embedding depth | 34 mm |
| Depth | 54 mm |
| Width | 70.9 mm |
| Height | 70.9 mm |
| Net weight | 0.1215 kg |

Environment

| | |
|---------------------------------|--|
| IK degree of protection | IK01 |
| IP degree of protection | IP20 |
| Environmental characteristic | UV resistant Ammonia Acetone Window-cleaning fluid Liquid soap Oil Bleach Petrol Alcohol |
| Environmental health and issues | Halogen free |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 172.9 g |
| Package 1 Height | 6.2 cm |
| Package 1 width | 9.5 cm |
| Package 1 Length | 10.6 cm |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 15 |
| Package 2 Weight | 2.98 kg |
| Package 2 Height | 15 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|