



Main

Range	Unica
Device application	Mounting
Product or component type	Mounting box
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Number of modules	2 x 4 modules
Fixing mode	Clip-in
Colour tint	Yellow

Complementary

Device mounting	Flush
Cable entry	16 knock-outs
Material	ABS (acrylonitrile butadiene-styrene): box
Standards	ISO 8015
Depth	40 mm
Width	135 mm
Height	135 mm
Net weight	54.8 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil UV resistant Liquid soap Petrol Bleach Alcohol

Ammonia
Window-cleaning fluid
Acetone

Environmental health and issues	Halogen free
---------------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	76 g
Package 1 Height	5.4 cm
Package 1 width	16 cm
Package 1 Length	14.1 cm
Unit Type of Package 2	S01
Number of Units in Package 2	6
Package 2 Weight	638 g
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	192
Package 3 Weight	30.29 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------