



❗ Discontinued

Main

Range	TeSys
Device short name	GK2AX
Product or component type	Auxiliary contact block
Product compatibility	GK3EF
Mounting location	Right side
Pole contact composition	1 NO
Connections - terminals	Screw clamp terminals 1 cable(s) 1...4 mm ² solid Screw clamp terminals 1 cable(s) 2.5 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 2.5 mm ² flexible with cable end
Quantity per set	Set of 10

Complementary

Standards	500 V conforming to IEC 60947-1
Control type	Manual test
[Ue] rated operational voltage	500 V
Protection type	GB2CB... circuit breaker GG fuse 6 A
Utilisation category	360 VA at 48 V AC-15 - electrical durability: 20000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 20000 cycles 800 VA at 220...240 V AC-15 - electrical durability: 20000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 20000 cycles 700 VA at 440 V AC-15 - electrical durability: 20000 cycles 700 VA at 500 V AC-15 - electrical durability: 20000 cycles
Utilisation category	180 W at 24 V DC-13 - electrical durability: 1000 cycles 240 W at 48 V DC-13 - electrical durability: 1000 cycles 180 W at 60 V DC-13 - electrical durability: 1000 cycles 140 W at 110 V DC-13 - electrical durability: 1000 cycles 120 W at 220 V DC-13 - electrical durability: 1000 cycles
Connections - terminals	0.8 N.m - on screw clamp terminals

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Packing Units

Package 1 Weight	0.034 kg
Package 1 Height	0.750 dm
Package 1 width	0.100 dm
Package 1 Length	0.800 dm

Contractual warranty

Warranty	18 months
----------	-----------

GK2AX10



GK2AX10 is replaced by:



Add-on auxiliary blocks GVAE1

TeSys GV2 & GV3 - auxiliary contact - 1 NO/NC

Qty 1

Reason for Substitution: End of life | Substitution date: 29 April 2009
