



Main

Range	TeSys
Device short name	GV3A
Product or component type	Auxiliary contact block
Product compatibility	GV3ME
Mounting location	Front side
Auxiliary contacts operation	Fault signal 1 NO
Pole contact composition	1 NO
Connections - terminals	Screw clamp terminals 1 cable(s) 1...2.5 mm ² solid Screw clamp terminals 2 cable(s) 1...2.5 mm ² solid Screw clamp terminals 1 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.75...2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.75...1.5 mm ² flexible with cable end
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	600 V conforming to UL 508 690 V conforming to IEC 60947-1 600 V conforming to CSA C22.2 No 14
[Ue] rated operational voltage	48...690 V AC 24...220 V DC
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker GG fuse 6 A
Mechanical durability	1000 cycles
Rated operational power in VA	240 VA at 48 V AC-11 - electrical durability: 1000 cycles 450 VA at 440 V AC-11 - electrical durability: 1000 cycles 450 VA at 500 V AC-11 - electrical durability: 1000 cycles 200 VA at 690 V AC-11 - electrical durability: 1000 cycles 460 VA at 110...127 V AC-11 - electrical durability: 1000 cycles 800 VA at 220...240 V AC-11 - electrical durability: 1000 cycles 850 VA at 380...415 V AC-11 - electrical durability: 1000 cycles
Rated operational power in W	180 W at 24 V DC-11 - electrical durability: 1000 cycles 180 W at 48 V DC-11 - electrical durability: 1000 cycles 135 W at 60 V DC-11 - electrical durability: 1000 cycles

105 W at 110 V DC-11 - electrical durability: 1000 cycles
90 W at 220 V DC-11 - electrical durability: 1000 cycles

Width	9 mm
-------	------

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	23 g
Package 1 Height	3.4 cm
Package 1 width	7 cm
Package 1 Length	7.4 cm
Unit Type of Package 2	S01
Number of Units in Package 2	60
Package 2 Weight	1.584 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------