



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Utilisation category	18 A AC-3
Device composition	Thermal overload relay ordered separately Reversing contactor
Network type	10 kW at 500 V AC 50/60 Hz 10 kW at 660/690 V AC 50/60 Hz 4 kW at 220/230 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 7.5 kW at 380/400 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Push-button stop/reset red O Selector switch 2 positions start I-II

Complementary

Location	2 ISO20 top 2 ISO25 top 2 Pg 16 bottom 2 Pg 21 bottom 2 ISO20 bottom 2 ISO25 bottom
----------	--

Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529

IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	2.410 kg
Package 1 Height	2.600 dm
Package 1 width	2.900 dm
Package 1 Length	4.000 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------