

910 COAXIAL CABLES

RG-11 Cables

CL-201

CL-200



Description

RG-11 coaxial cable with physically expanded dielectric. Flame-retardant. Conforms to norm EN 50117.

Applications

Used to transmit the TV signal in the terrestrial band or in the satellite IF band in distributions requiring substantial lengths of cable.

Characteristics

Supplied in coils of 250 m and packed in a carton box.

CODE		9100057		9100016	
MODEL		CL-201		CL-200	
Internal conductor	Mat	CU			
	mmø	1.63			
Dielectric	Mat	PEE Physical			
	mmø	7.20			
Shielding	Mat	CU		AL	
Mesh	Mat	CU		AL	
Cover	Mat	PE black			
	mmø	10			
Attenuation / 100m	dB	50 MHz	2.7		3.0
		470 MHz	7.6		8.7
		862 MHz	11.0		12.6
		2150 MHz	20.0		21.5
Return loss	dB	5-470 MHz	>23		
		470-2150 MHz	>20		
Resistance to DC current	Ω/Km	34		37	
Minimum bending radius	mm	35			
Characteristic impedance	Ω	75 ±3,0			
Units per packing		250		200	
Packing weight	Kg			15.0	
Packing dimensions	mm	400 x 400 x 370		450 x 450 x 300	