




<b>DIMENSIONS (Cm)</b>	<b>Effective</b> 105 x 120 x h.90
	<b>On Pallet</b> 105 x 120 x h.105
<b>WEIGHT (Kg)</b>	<b>Effective</b> 620
	<b>On Pallet</b> 635
<b>OIL</b>	SAE = 40
	Quantity = 14 lt.
<b>ELECTRIC MOTOR</b>	400V - 50HZ
	5,5 HP - 4 kW
<b>RPM</b>	6

	R. = 65 Kg. / mm <sup>2</sup>			R. = 85 Kg. / mm <sup>2</sup>		
<b>Cutting capability</b>	1 Ø 32	2 Ø 22	3 Ø 18	1 Ø 30	2 Ø 20	3 Ø 16
<b>Bending capability</b>	1 Ø 38	2 Ø 28	3 Ø 22	1 Ø 36	2 Ø 25	3 Ø 20

### STANDARD EQUIPMENT

#### BLADES

On each cutting machine, 2 hardened steel blades are already fitted.



#### BIGGER ROTATING PLATE DIMENSION: Ø460 mm

It can support bushes up to Ø 260 mm to realize bending of big radius without need of extra equipments (Special Arm for large radii).



1 hardened square pin; 1 hardened stirrup bending pin;  
3 hardened bush holding pins; 1 checking block; 1 pedal;  
5 bushes Ø60-70-80-95-120 mm; 1 set Allen keys.  
2 Long Saddles, indispensable to realize the "double bend"!

### OPTIONALS



#### "UNIQUE 2 in 1"

To bend more stirrups simultaneously and determine the length from the bending point.



#### Spirals/Hoops Device:

Allows to realize spiral/hoop armatures with bars Ø max.16 mm.



#### "Basic Angle Control" Panel:

Allows to set up manually 6 bending angles, that will be carried out in sequence.



#### "Angle Control" Panel:

This special computer permits to program up to 20 bending angles in very rapid and intuitive way.



**2-Speed Motor:** Available on request for those who work bars of different diameters and want to optimize production times.



#### Special Bushes for large radii.



**Working top "Type B":** The cover in sheet metal prevents the turning plate from dust and material residuals.



#### Roller Bench:

To deposit and move the material. Available in different lengths, as needed.