


Punte elicoidali cilindriche rettificate a doppio conoide 

HSS-G fully ground twist drills "Speedmaster®" / Forets cylindriques rectifiés "Speedmaster®"

Brocas helicoidales rectificadas "Speedmaster®" / Geschliffene Spiralbohrer "Speedmaster®"

 HSS-G DIN 338 Rettificata / Ground from the solid / Rectifié / Rectificada / Geschliffen

01220



Doppio conoide  
Double conoid  
SPLIT POINT  
(Ø ≈ 2,5 mm)

AISI M2  
HV ≈ 820÷850

Confezione / Packaging



Applicazioni / Applications

R ≤ 900 N/mm²




Taglio altamente professionale con trapani portatili o stazionari in: acciai legati ed altamente legati, acciaio inox fino a R ≤ 900 N/mm², ferro, alluminio, metalli.

High quality cuts with portable or bench drilling machines into: alloy steel, high alloy steel, stainless steel up to R ≤ 900 N/mm², iron, aluminium, metals.

Très professionnel découpage avec trépan portatifs ou (stationnaires) en: acier, acier inox jusqu'à R ≤ 900 N/mm, fer, aluminium et métaux.

Corte altamente profesional con taladros portátiles o estacionarios en: aceros aleados y altamente aleados, acero inox hasta R ≤ 900 N/mm², hierro, aluminio, metales.

Beruflicher Schnitt mit tragbaren Bohrers in: legiert und unlegiert Stahl, rostfreier Stahl bis R ≤ 900 N/mm², Aluminium, Eisen.

Ø h8	/	L	pcs 	cod.	€ each/cad.
1	12	34	10	012200100	
1,25	16	38	10	012200125	
1,5	18	40	10	012200150	
1,75	22	46	10	012200175	
2	24	49	10	012200200	
2,25	27	53	10	012200225	
2,5	30	57	10	012200250	
2,75	33	61	10	012200275	
3	33	61	10	012200300	
3,25	36	65	10	012200325	
3,5	39	70	10	012200350	
3,75	39	70	10	012200375	
4	43	75	10	012200400	
4,25	43	75	10	012200425	
4,5	47	80	10	012200450	
4,75	47	80	10	012200475	
5	52	86	10	012200500	
5,1	52	86	10	012200510	
5,25	52	86	10	012200525	
5,5	57	93	10	012200550	
5,75	57	93	10	012200575	
6	57	93	10	012200600	
6,25	63	101	10	012200625	
6,5	63	101	10	012200650	
6,75	69	109	10	012200675	
7	69	109	10	012200700	
7,25	69	109	5	012200725	
7,5	69	109	5	012200750	
7,75	75	117	5	012200775	
8	75	117	5	012200800	
8,25	75	117	5	012200825	
8,5	75	117	5	012200850	
8,75	81	125	5	012200875	
9	81	125	5	012200900	
9,25	81	125	5	012200925	
9,5	81	125	5	012200950	
9,75	87	133	5	012200975	
10	87	133	5	012201000	
10,25	87	133	5	012201025	
10,5	87	133	5	012201050	
10,75	94	142	5	012201075	
11	94	142	5	012201100	
11,25	94	142	5	012201125	
11,5	94	142	5	012201150	
11,75	94	142	5	012201175	
12	101	151	5	012201200	
12,25	101	151	5	012201225	
12,5	101	151	5	012201250	
12,75	101	151	5	012201275	
13	101	151	5	012201300	

Abs



19 pcs  
Ø 1÷10 x 0,5 mm

01229301 €



25 pcs  
Ø 1÷13 x 0,5 mm

01229302 €

Caratteristiche tecniche / Technical features

**3 pianetti antiscivolo (Ø > 5 mm):**  
Piena trasmissione della potenza  
- 3 anti-skid flats (Ø > 5 mm):  
Full power transmission  
- 3 plats antirotation (Ø > 5 mm):  
Plain transmission de la puissance  
- 3 planos antiresbaladizo (Ø > 5 mm):  
Llena transmisión de la potencia  
3 rutschsicheren Pläne - volle Übermittlung von der Macht.

**Cave ampie e lisce:**  
Facile estrazione dei trucioli  
Wide and smooth flutes:  
Easy chip removal  
Rainures grandes et lisses:  
Evacuation facile des copeaux  
Ranuras anchas y lisas:  
Fácil extracción de las virutas  
Weiten und glatten Furchen :  
einfacher Auszug des Hobelspannes.

**Affilatura speciale**  
Special Sharpening  
Affûtage Spécial  
Affiladura especial  
Besonderes Schleifen.

