

Forets à béton "Super Granit" pour percer granit, la pierre naturelle, Betão, etc.

03110

DIN 8039 ISO 5468
Fraisé

Spécial pour les matériaux de construction durs



Emballage



Ø mm	pouces	d	l	L	uds.	cód.
3	1/8	2,8	30	60	1	031100300
4	5/32	3,8	40	75	1	031100400
5	3/16	4,5	50	75	1	031100500
6	15/64	5,5	60	100	1	031100600
7	9/32	6,5	60	100	1	031100700
8	5/16	7,5	80	120	1	031100800
9	23/64	8	80	120	1	031100900
10	25/64	9	80	120	1	031101000
11	7/16	10	90	150	1	031101100
12	15/32	10	90	150	1	031101200
13	1/2	10	90	150	1	031101300
14	9/16	10	90	150	1	031101400
15	19/32	10	100	160	1	031101500
16	5/8	12	100	160	1	031101600
18	23/32	12	100	160	1	031101800
20	25/32	12	100	160	1	031102000

Applications



Granit



Béton



Pierre

Pour perçage à fort percussion in granit, pierre naturelle et artificielle, ciment, carrelage (7° MOHS).

Grande goujure fraisée de type "U" pour un dépoussiérage efficace. Affûtage au diamant. Corps en acier allié avec HRC 40÷50. Température de brasage à 1100° C.