


01146**HSS-CO 5%****DIN 338**

Queue réduite - 13mm



Emballage



Ø h8	l	L	d	 uds.	cód.
13,25	108	160	13	3	011461325
13,5	108	160	13	3	011461350
13,75	108	160	13	3	011461375
14	108	160	13	3	011461400
14,25	114	169	13	3	011461425
14,5	114	169	13	3	011461450
14,75	114	169	13	3	011461475
15	114	169	13	3	011461500
15,25	120	178	13	3	011461525
15,5	120	178	13	3	011461550
15,75	120	178	13	3	011461575
16	120	178	13	3	011461600
16,5	125	184	13	1	011461650
17	125	184	13	1	011461700
17,5	130	191	13	1	011461750
18	130	191	13	1	011461800
18,5	135	198	13	1	011461850
19	135	198	13	1	011461900
19,5	140	205	13	1	011461950
20	140	205	13	1	011462000
20,5	145	213	13	1	011462050
21	145	213	13	1	011462100
21,5	150	221	13	1	011462150
22	150	221	13	1	011462200
22,5	150	221	13	1	011462250
23	155	229	13	1	011462300
23,5	155	229	13	1	011462350
24	160	236	13	1	011462400
24,5	160	236	13	1	011462450
25	160	236	13	1	011462500

 $R \leq 1200 \text{ N/mm}^2$

Applications



Inox



Métaux



Acier



Emulsion

2.

Pour percer l'acier allié, la fonte, l'acier inox avec $R \leq 1200 \text{ N/mm}^2$.