

01020**HSS-R****DIN 340**
Laminé

Série longue



W 27°



HV = 750÷820



<8 d



Emballage

**R ≤ 650 N/mm²**

Applications



Métaux



Acier



Emulsion

**Artigo 01021 Self**

Sur demande

Ø	l	L	uds.	cód.
1,5	45	70	10	010200150
1,75	53	80	10	010200175
2	56	85	10	010200200
2,2	59	90	10	010200220
2,25	59	90	10	010200225
2,5	62	95	10	010200250
2,75	66	100	10	010200275
2,8	66	100	10	010200280
3	66	100	10	010200300
3,2	69	106	10	010200320
3,25	69	106	10	010200325
3,5	73	112	10	010200350
3,75	73	112	10	010200375
3,8	78	119	10	010200380
4	78	119	10	010200400
4,2	78	119	10	010200420
4,25	78	119	10	010200425
4,5	82	126	10	010200450
4,75	82	126	10	010200475
4,8	87	132	10	010200480
5	87	132	10	010200500
5,2	87	132	10	010200520
5,25	87	132	10	010200525
5,5	91	139	10	010200550
5,75	91	139	10	010200575
5,8	91	139	10	010200580
6	91	139	10	010200600
6,25	97	148	5	010200625
6,5	97	148	5	010200650
6,75	97	148	5	010200675
7	102	156	5	010200700
7,25	102	156	5	010200725
7,5	102	156	5	010200750
7,75	109	165	5	010200775
8	109	165	5	010200800
8,25	109	165	5	010200825
8,5	109	165	5	010200850
8,75	115	175	5	010200875
9	115	175	5	010200900
9,25	115	175	5	010200925
9,5	115	175	5	010200950
9,75	121	184	5	010200975
10	121	184	5	010201000
10,5	121	184	5	010201050
11	128	195	5	010201100
11,5	128	195	5	010201150
12	134	205	5	010201200
12,5	134	205	5	010201250
13	134	205	5	010201300
13,5	140	214	3	010201350
14	140	214	3	010201400
14,5	144	220	3	010201450
15	144	220	3	010201500
15,5	149	227	3	010201550
16	149	227	3	010201600
17	154	235	1	010201700
18	158	241	1	010201800
19	162	247	1	010201900
20	166	254	1	010202000

Pour percer: fer, acier, métaux...

