

## Punte elicoidali cilindriche serie lunga, interamente rettificate

Long straight shank twist drills / Forets cylindriques série longue

Brocas helicoidales serie larga / Spiralbohrer, lange Ausführung

### HSS-G DIN 340 Rettificata / Ground from the solid / Rectifié / Rectificada / Geschliffen

01096



| Ø<br>h8 | /   | L   | pcs<br> | cod.      | €<br>cad/each |
|---------|-----|-----|---------|-----------|---------------|
| 1       | 33  | 56  | 10      | 010960100 |               |
| 1,5     | 45  | 70  | 10      | 010960150 |               |
| 1,75    | 53  | 80  | 10      | 010960175 |               |
| 2       | 56  | 85  | 10      | 010960200 |               |
| 2,25    | 59  | 90  | 10      | 010960225 |               |
| 2,5     | 62  | 95  | 10      | 010960250 |               |
| 2,75    | 66  | 100 | 10      | 010960275 |               |
| 3       | 66  | 100 | 10      | 010960300 |               |
| 3,25    | 69  | 106 | 10      | 010960325 |               |
| 3,5     | 73  | 112 | 10      | 010960350 |               |
| 3,75    | 73  | 112 | 10      | 010960375 |               |
| 4       | 78  | 119 | 10      | 010960400 |               |
| 4,25    | 78  | 119 | 10      | 010960425 |               |
| 4,5     | 82  | 126 | 10      | 010960450 |               |
| 4,75    | 82  | 126 | 10      | 010960475 |               |
| 5       | 87  | 132 | 10      | 010960500 |               |
| 5,25    | 87  | 132 | 10      | 010960525 |               |
| 5,5     | 91  | 139 | 10      | 010960550 |               |
| 5,75    | 91  | 139 | 10      | 010960575 |               |
| 6       | 91  | 139 | 10      | 010960600 |               |
| 6,25    | 97  | 148 | 5       | 010960625 |               |
| 6,5     | 97  | 148 | 5       | 010960650 |               |
| 6,75    | 97  | 148 | 5       | 010960675 |               |
| 7       | 102 | 156 | 5       | 010960700 |               |
| 7,25    | 102 | 156 | 5       | 010960725 |               |
| 7,5     | 102 | 156 | 5       | 010960750 |               |
| 7,75    | 109 | 165 | 5       | 010960775 |               |
| 8       | 109 | 165 | 5       | 010960800 |               |
| 8,25    | 109 | 165 | 5       | 010960825 |               |
| 8,5     | 109 | 165 | 5       | 010960850 |               |
| 8,75    | 115 | 175 | 5       | 010960875 |               |
| 9       | 115 | 175 | 5       | 010960900 |               |
| 9,25    | 115 | 175 | 5       | 010960925 |               |
| 9,5     | 115 | 175 | 5       | 010960950 |               |
| 9,75    | 121 | 184 | 5       | 010960975 |               |
| 10      | 121 | 184 | 5       | 010961000 |               |
| 10,5    | 121 | 184 | 5       | 010961050 |               |
| 11      | 128 | 195 | 5       | 010961100 |               |
| 11,5    | 128 | 195 | 5       | 010961150 |               |
| 12      | 134 | 205 | 5       | 010961200 |               |
| 12,5    | 134 | 205 | 5       | 010961250 |               |
| 13      | 134 | 205 | 5       | 010961300 |               |
| 13,5    | 140 | 214 | 3       | 010961350 |               |
| 14      | 140 | 214 | 3       | 010961400 |               |
| 14,5    | 144 | 220 | 3       | 010961450 |               |
| 15      | 144 | 220 | 3       | 010961500 |               |
| 15,5    | 149 | 227 | 3       | 010961550 |               |
| 16      | 149 | 227 | 3       | 010961600 |               |
| 16,5    | 154 | 235 | 1       | 010961650 |               |
| 17      | 154 | 235 | 1       | 010961700 |               |
| 17,5    | 158 | 241 | 1       | 010961750 |               |
| 18      | 158 | 241 | 1       | 010961800 |               |
| 18,5    | 162 | 247 | 1       | 010961850 |               |
| 19      | 162 | 247 | 1       | 010961900 |               |
| 19,5    | 166 | 254 | 1       | 010961950 |               |
| 20      | 166 | 254 | 1       | 010962000 |               |

Confezione / Packaging



Applicazioni / Applications

R ≈ 800 N/mm<sup>2</sup>

