

01096**HSS-G****DIN 340**
Rectifié

Série longue



W 27°

HV 820
SPLIT POINT
DIN 1412C
(Ø≥3)

<8 d

Emballage

**R ≤ 800 N/mm²**

Applications




Acier



Métaux



Emulsion



Ø h8	l	L	 uds.	cód.
1	33	56	10	010960100
1,5	45	70	10	010960150
1,75	53	80	10	010960175
2	56	85	10	010960200
2,25	59	90	10	010960225
2,5	62	95	10	010960250
2,75	66	100	10	010960275
3	66	100	10	010960300
3,25	69	106	10	010960325
3,5	73	112	10	010960350
3,75	73	112	10	010960375
4	78	119	10	010960400
4,25	78	119	10	010960425
4,5	82	126	10	010960450
4,75	82	126	10	010960475
5	87	132	10	010960500
5,25	87	132	10	010960525
5,5	91	139	10	010960550
5,75	91	139	10	010960575
6	91	139	10	010960600
6,25	97	148	5	010960625
6,5	97	148	5	010960650
6,75	97	148	5	010960675
7	102	156	5	010960700
7,25	102	156	5	010960725
7,5	102	156	5	010960750
7,75	109	165	5	010960775
8	109	165	5	010960800
8,25	109	165	5	010960825
8,5	109	165	5	010960850
8,75	115	175	5	010960875
9	115	175	5	010960900
9,25	115	175	5	010960925
9,5	115	175	5	010960950
9,75	121	184	5	010960975
10	121	184	5	010961000
10,25	121	184	5	010961025
10,5	121	184	5	010961050
10,75	121	184	5	010961075
11	128	195	5	010961100
11,25	128	195	5	010961125
11,5	128	195	5	010961150
11,75	128	195	5	010961175
11,8	128	195	5	010961180
12	134	205	5	010961200
12,25	134	205	5	010961225
12,5	134	205	5	010961250
12,75	134	205	5	010961275
13	134	205	5	010961300
13,5	140	214	3	010961350
14	140	214	3	010961400
14,5	144	220	3	010961450
15	144	220	3	010961500
15,5	149	227	3	010961550
16	149	227	3	010961600
16,5	154	235	1	010961650
17	154	235	1	010961700
17,5	158	241	1	010961750
18	158	241	1	010961800
18,5	162	247	1	010961850
19	162	247	1	010961900
19,5	166	254	1	010961950
20	166	254	1	010962000