

Lanyards, Safety Set

Lanyards

Lanyards with standard length of 1.5 meter are used for support / restraint applications. Webbing and Rope lanyards are available along with any combination of connectors.

WL2060 Weight: 0.8 kg 	RL15 Weight: 0.4 kg 
WL1560 Weight: 0.8 kg 	NR2060 Weight: 0.8 kg 
WLK2560 Weight: 0.6 kg 	NR1515 Weight: 0.6 kg 
RL1560 Weight: 0.8 kg 	DNR1560 Weight: 1.4 kg  1.5m
RL1515 Weight: 0.6 kg 	

H2000 - Safety Set 2



Features:

- According to EN 361, 355 and EN 353 / 2
- CE approved – CE 0082
- 15 M 12 mm non-rotative rope
- 1 Safety Harness Ref. H2000 / 2
- 1 Fall Arrest Device
- 1 Shock Absorber Ref. SFAD
- 2 Safety Hooks CT15
- 1 Metal Box
- Weight: 11 kg

For vertical application only



H2000 - Safety Set 3



Features:

- According to EN 361, 355, 358 and EN 353 / 2
- CE approved – CE 0082
- 15 M 12 mm non-rotative rope
- 1 Safety Harness Ref. H2000 / 3
- 1 Fall Arrest Device
- 1 Shock Absorber Ref. SFAD
- 2 Safety Hooks CT15
- 1 Metal Box
- Weight: 10 kg

For vertical application only



- Different models of harness can be provided with Safety Set.
- Any combination of connectors is possible.
- Different lengths of rope can be provided with Safety Set.