


Maillon de jonction démontable - bague à ressort


GRADE 80



Réf.	Diam. (mm)	CMU (t)	A (mm)	d (mm)	E (mm)	F (mm)	L (mm)	Poids (kg)	Code art.
MAJOA01106	6	1,12	15	8	23	15	46	0,07	
MAJOA02007	7	1,5	20	9	29	20	58	0,15	
MAJOA02008	8	2	20	11	28	20	58	0,16	
MAJOA03110	10	3,15	25	11,5	34,5	24	69	0,3	
MAJOA05313	13	5,3	30	16	42	27	84	0,6	
MAJOA08016	16	8	35	22	51	32	102	1,2	
MAJOA12520	18/20	12,5	40	24	60	41	120	1,9	
MAJO15022	22	15	45	27	70	53	140	2,8	
MAJO21226	24/26	21,2	50	32	75	57	150	4,2	
MAJO3132	32	31,5	55	40	86	67	172	8,4	

Maillon de jonction chaîne/sangle - bague à ressort type A13


GRADE 80



Réf.	Diam. chaîne (mm)	Diam. sangle (mm)	CMU (t)	H (mm)	L (mm)	S (mm)	B (mm)	P (mm)	E (mm)	Poids (kg)	Code art.
A 1302	7/8	50	2	65	50	26	22	20	9	0,3	
A 1303	10	59	3,15	76	59	31	26	25	11	0,52	
A 1304	13	75	5,3	92	75	35	31	26	15	1	

Maillon U-link type U


GRADE 80



Réf.	Diam. chaîne (mm)	Diam. sangle (mm)	CMU (t)	A (mm)	E (mm)	H (mm)	S (mm)	Poids (kg)	Code art.
U 6	6	22	1,12	23	34	12	9	0,07	
U 8	7/8	25	2	26	40	14,5	12	0,13	
U 10	10	30	3,15	31,5	53	17,5	15	0,24	
U 13	13	40	5,3	42	65	21	20,5	0,47	
U 16	16	53	8	53	83	28	26	0,92	

Manille oméga

GRADE 80



Réf.	Diam. chaîne (mm)	Diam. sangle (mm)	CMU (t)	A (mm)	E (mm)	H (mm)	S (mm)	Poids (kg)	Code art.
COUP01	6	7/32	1,12	18	25	11	9	0,07	
COUP02	7/8	5/16	2	22	35	16	12	0,17	
COUP03	10	3/8	3,15	28	41	16	15	0,28	
COUP05	13	1/2	5,3	38	53	21	20	0,6	
COUP08	16	5/8	8	46	66	28,5	25	1,15	
COUP012	18/20	3/4	12,5	56	81	35	30	2	