


82H - Clés mâles courtes métriques




NF ISO 2936, ISO 2936, DIN ISO 2936, ASME B18.3.2M

- Fabriquée en acier au silicium.
- Présentation : phosphatée.

82H	A [mm]	L [mm]	H [mm]	ΔΔ [g]
82H.0,9	0,9	38	12	0,30
82H.1,3	1,3	45	13	0,70
82H.1,5	1,5	45	13	0,90
82H.2	2,0	50	16	2,00
82H.2,5	2,5	62	17	3,00
82H.3	3,0	65	20	5,00
82H.3,5	3,5	66	22	8,00
82H.4	4,0	70	25	10,00
82H.4,5	4,5	75	26	15,00
82H.5	5,0	80	28	20,00
82H.6	6,0	90	32	30,00
82H.7	7,0	95	34	45,00
82H.8	8,0	100	36	60,00
82H.9	9,0	105	38	80,00
82H.10	10,0	112	40	100,00
82H.11	11,0	118	42	130,00
82H.12	12,0	125	45	165,00
82H.13	13,0	135	50	205,00
82H.14	14,0	140	55	260,00
82H.15	15,0	150	58	310,00
82H.16	16,0	154	60	370,00
82H.17	17,0	160	63	440,00
82H.18	18,0	170	66	540,00
82H.19	19,0	180	70	640,00
82H.22	22,0	200	80	950,00
82H.23	23,0	210	85	1100,00
82H.24	24,0	224	90	1250,00
82H.27	27,0	250	100	1300,00
82H.32	32,0	315	125	1420,00

82H - Clés mâles courtes en pouces



- Fabriquée en acier au silicium.
- Présentation : phosphatée.

82H	A ["]	L [mm]	H [mm]	ΔΔ [g]
82H.028	0,28	33	10	0,30
82H.050	0,50	38	12	0,40
82H.3/64	3/64	38	12	0,50
82H.1/16	1/16	45	13	0,70
82H.5/64	5/64	50	16	2,00
82H.3/32	3/32	62	17	3,00
82H.7/64	7/64	60	18	4,00
82H.1/8	1/8	65	20	6,00
82H.9/64	9/64	66	22	8,00
82H.5/32	5/32	70	25	10,00
82H.3/16	3/16	80	28	16,00
82H.7/32	7/32	90	32	24,00
82H.1/4	1/4	90	32	33,00
82H.5/16	5/16	100	36	59,00
82H.3/8	3/8	112	40	90,00
82H.7/16	7/16	118	42	135,00
82H.1/2	1/2	125	45	202,00
82H.9/16	9/16	140	55	273,00
82H.5/8	5/8	160	60	383,00
82H.11/16	11/16	170	63	540,00
82H.3/4	3/4	175	70	623,00
82H.7/8	7/8	200	80	955,00
82H.1'	1'	235	90	1450,00

