

# R25 (1")

# Drifting, tunnelling and bolting

## Shank end rods



Fully carburized.

Length (L)		Product No.	Product code	Seal Product No.	Seal Product code	Weight approx. kg
mm	foot/inch					
<b>Shank hex. 22 mm (7/8") × 108 mm (4 1/4"). 25 mm (1") thread. Flushing hole diameter 8,6 mm.</b>						
265	10 3/8"	90000237	502-0103-06-C,02	90002182	9232	1,2
610	2'	90570115	502-0106-06-C,02	90002182	9232	2,3
760	2' 5 7/8"	90510004	502-0108-06-C,02	90002182	9232	2,9
1000	3' 3 3/8"	90531258	502-0110-06-C,02	90002182	9232	3,4
1200	3' 11 1/4"	90580089	502-0112-06-C,02	90002182	9232	4,5
1600	5' 3"	90514336	502-0116-06-C,02	90002182	9232	5,7
1830	6'	90500017	502-0118-06-C,02	90002182	9232	6,1
2400	7' 10 1/2"	90513918	502-0124-C,02	–	–	7,9
2435	8'	90510009	502-0124-06-C,02	90002182	9232	7,9
3200	10' 6"	90513919	502-0132-C,02	–	–	10,4
3200	10' 6"	90500012	502-0132-06-C,02	90002182	9232	10,4
3600	11' 9 3/4"	90510785	502-0136-C,02	–	–	11,8
4000	13' 1 1/2"	90502700	502-0140-06-C,02	90002182	9232	13,0
<b>Shank hex. 25 mm (1") × 108 mm (4 1/4"). 25 mm (1") thread. Flushing hole diameter 8,6 mm.</b>						
255	10"	90000240	502-1203-C,02	90000378	9150-08	1,4
610	2'	90505425	502-1206-C,02	90000378	9150-08	3,1
1200	3' 11 1/4"	90505424	502-1212-C,02	90000378	9150-08	5,1
1830	6'	90505423	502-1218-C,02	90000378	9150-08	7,7
2435	8'	90500568	502-1224-C,02	90000378	9150-08	9,5
<b>Shank hex. 25 mm (1") × 159 mm (6 1/4"). 25 mm (1") thread. Flushing hole diameter 8,6 mm.</b>						
255	10"	90000247	502-1503-C,02	90000378	9150-08	1,6
610	2'	90510516	502-1506-C,02	90000378	9150-08	3,1
800	2' 7 1/2"	90513915	502-1508-C,02	90000378	9150-08	4,1
3200	10' 6"	90000986	502-1532-C,02	90000378	9150-08	13,2