



参数

TECHNICAL PARAMETERS

	型号model		EJC210-20	EJC210-25	EJC212-30	EJC212-35
特性	驾驶形式operating type		步行式walkie	步行式walkie	步行式walkie	步行式walkie
	动力源power source		蓄电池battery	蓄电池battery	蓄电池battery	蓄电池battery
	额定载重load capacity	Kg	1000	1000	1200	1200
	载荷中心距load center	mm	600	600	600	600
	轮子类型wheel type		PU	PU	PU	PU
	自重service weight	Kg	530	554	580	610
	尺寸	轮子尺寸 (驱动轮/从动轮/承重轮)Wheel dimension(driving wheel/balance wheel/bearing wheel)	mm	φ210x70/φ115x55/φ80x70		
轴距wheel base		mm	1146.5	1146.5	1146.5	1146.5
轮子数量 (驱动轮/从动轮/承重轮) Wheel quantity(driving wheel/balance wheel/bearing wheel)		pcs	1/1/4	1/1/4	1/1/4	1/1/4
操作手柄高度 (最高/最低) Operate handle(highest/lowest)		mm	1185/840	1185/840	1185/840	1185/840
整车长度/宽度 Overall length/width		mm	1696/790	1696/790	1696/790	1696/790
货叉尺寸 (厚/宽/长) Fork dimension(thickness/width/length)		mm	60/185/1150	60/185/1150	60/185/1150	60/185/1150
货叉间距 (内侧/外侧) Width between forks(inside/outside)		mm	185/555	185/555	185/555	185/555
最小离地间隙 min. ground clearance		mm	30	30	30	30
起升高度 fork lift height		mm	2000	2500	3000	3500
性能		最小转弯半径 min.turning radius	mm	1325	1325	1325
	直角堆垛通道通过宽度 (最小) Min.aisle width for pallets	mm	2018	2018	2018	2018
	最大爬坡度 (满载/空载) Gradeability (laden/unladen)	%	5/7	5/7	5/7	5/7
	最大行驶速度 (满载/空载) Travel speed(laden/unladen)	Km/h	3.5/4.0	3.5/4.0	3.5/4.0	3.5/4.0
	起升速度 (满载/空载) Lift speed(laden/unladen)	mm/s	110/160	110/160	110/160	110/160
	下降速度 (满载/空载) Lowering speed(laden/unladen)	mm/s	155/170	155/170	155/170	155/170
	制动方式 (行车/驻车) Brake type		电磁Electromagnetic	电磁Electromagnetic	电磁Electromagnetic	电磁Electromagnetic
	驱动电机 (直流) drive motor(DC)	Kw	0.75	0.75	0.75	0.75
	提升电机 (直流) lift motor(DC)	Kw	2.2	2.2	2.2	2.2
	蓄电池电压battery voltage	V	24	24	24	24
蓄电池容量battery capacity	Ah	75x2	75x2	75x2	75x2	