

## Corrugated PVC suction hose



- Smooth inner surface and corrugated outer surface
- Corrugated outer surface provide high flexibility and small bending radius.
- Transparent PVC layer will enable better visibility of flowing material inside
- Working Temperature:-5°Cto +65°C

### Application !

Made of quality PVC reinforced with integral helix of rigid PVC, excellent for conveying and suction of water, oil, powder and dust in pump industries, constructions and other applications.

### Specification !

PRODUCT CODE	ID		OD	WP		BP		W/A	COIL
	inch	mm	mm	bar	psi	bar	psi	g/m	m
ET-CSH-025	1	25	31	11	165	33	495	220	50
ET-CSH-032	1-1/4	32	38	9	135	27	405	270	50
ET-CSH-038	1-1/2	38	46	9	135	27	405	410	50
ET-CSH-050	2	50	60	9	135	27	405	650	50
ET-CSH-063	2-1/2	63	73	8	120	24	360	900	50
ET-CSH-075	3	75	87	8	120	24	360	1260	50
ET-CSH-100	4	100	116	6	90	18	270	2020	30
ET-CSH-125	5	125	141	6	90	18	270	3270	30
ET-CSH-152	6	152	171	6	90	18	270	4050	20
ET-CSH-200	8	200	230	6	90	18	270	7200	10
ET-CSH-254	10	254	284	4	60	12	180	10500	10
ET-CSH-305	12	305	340	3.5	52.5	10.5	157.5	14500	10

