

<p>Conwave – SP2</p>	<p>Conwave SP2 is a dry pre mix, medium textured finishing coat. Special trowel application will provide a classic texture. Thickness is approximately 2-3 mm. Available in various colours.</p>	<p>Pre mixed SP2 is applied onto the prepared background to a thickness for approximately 2-3 mm, float finish with a plastic float, working over the surface in a circular, horizontal or vertical directions to achieve an even and textured decorative plaster.</p>	<p>50 kg bags</p>
<p>Decorative Cement Plaster – DCP2</p>	<p>DCP2 is a dry pre mix, ready to use pigmented decorative plaster that can be applied internally and externally.</p>	<p>DCP2 mixed as above can be applied in a single coat onto the prepared background up to a thickness of 18 mm and leveled by means of steel.</p>	<p>50 kg bags</p>
<p>Glitterlite</p>	<p>Glitterlite is a dry pre mix, decorative finish for internal and external use, giving a sparkling effect due to incorporated glass, silica sand and marble chips.</p>	<p>Apply a thin coat of Glitterlite to an approximate thickness of 5 mm onto the prepared surface with a steel trowel.</p>	<p>50 kg bags</p>

Roll Easy	Roll Easy SP1 is a dry pre mix, heavy or light textured finishing coat. It is a roller application for external or internal finishes. Thickness is approximately 1-1.5 mm. Available in various colours.	The mixed SP1 is applied to the prepared background to a thickness of 1.5 mm using a plastic roller. Light, medium or heavy textured finish can be obtained by moving the roller in a vertical or horizontal direction over the applied surface.	50 kg bags
Scratch Coat	Scratch Coat is a dry pre mix, pigmented decorative plaster that can be applied internally and externally.	Scratch Coat mixed as above can be applied, in a single coat, onto the prepared background to a thickness of 18 mm and levelled by means of a steel float.	50 kg bags
Tradition Plaster – ERP	ERP is a pre mix, pigmented mineral based decorative plaster for internal and external application.	Mixed ERP can be applied, in a single coat, onto the prepared background to a thickness of 18 mm, levelled and finished to achieve the required design.	50 kg bags