

Moulures

<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px; margin-right: 5px;">IP44</div> <div style="font-weight: bold; margin-right: 5px;">RoHS</div> </div>			Caractéristiques des Goulottes				Capacité des Câbles Isolés													
			Dim. Intérieures	Longueur	Section Intérieure (S)	Section Utile (Su)	∅ Utile Max.	Nbre Maximum Conducteurs H07 V-U												
L x H (mm)	Profil	Réf.	(mm)	(m)	(mm ²)	(S/1,4) (mm ²)	(mm)	1,5 mm ²	2,5 mm ²	4 mm ²	6 mm ²									
12 x 7		10010 CBR	10x5	2,10	61	44	5	5	4	3	2									
		10010 FBR																		
16 x 10		10020 CBR	14x8	2,10	121	86	8	11	7	6	4									
		10020 FBR																		
20 x 12,5		10030 CBR	18x10	2,10	182	130	10	16	11	9	6									
		10030 FBR																		
		10030 HBR																		
25 x 16		10450 CBR	23x14	2,10	290	207	14	25	18	14	11									
		10450 FBR																		
32 x 12,5		10410 CBR	30x10	2,10	310	221	10	13	9	7	5									
		10410 FBR																		
	10410 HBR																			
		10400 CBR										10	28	18	15	11				
10400 FBR																				
32 x 16		10040 CBR	30x14	2,10	401	286	14	36	25	20	15									
		10040 FBR																		
		10040 HBR																		
40 x 12,5		10050 CBR	38x9	2,10	394	282	9	16	11	9	6									
		10050 FBR					9	16	11	9	6									
	10050 HBR	9					36	24	19	14										
40 x 16		10060 CBR	38x14	2,10	514	368	14	21	14	11	8									
		10060 FBR					14	21	14	11	8									
	10060 HBR	14					47	32	25	19										
		10160 CBR					14	71	50	39	30									
10160 FBR																				
40 x 25		10480 CBR	37x22	2,10	805	575	22	71	50	39	30									
		10500 CBR										47x17	2,10	836	597	17	75	50	40	30
		10500 HBR																		
50 x 20		10510 CBR	47x17	2,10	256	183	17	49	33	26	20									
		10510 FBR					17	23	15	12	9									
	10520 CBR	17					23	15	12	9										
60 x 16		10070 CBR	57x14	2,10	787	563	14	20	14	11	8									
		10070 FBR					14	22	15	12	9									
	10070 HBR	14					20	14	11	8										
75 x 20		10170 CBR	72x18	2,10	325	232	17	29	20	16	12									
		10140 CBR					17	42	28	23	17									
		10140 FBR					17	29	20	16	12									

CBR - Complet Blanc; FBR - Complet Adhésif Blanc; HBR - Complet Blanc Sans Halogène.

Sans Halogène