



# Stucco Marbella

**Conmix Stucco Marbella**  
Interior marble finish



## Description

**Conmix Stucco Marbella is an acrylic emulsion based, specially formulated top coat marble effect coating for interior surface. Conmix Stucco Marbella can be applied in various finishes inspired from marble and other stone finishes.**



## Recommended Substrates

- Conmix Stucco Marbella is suitable for interior application on plaster walls, gypsum boards, block work, rendered surfaces, MDF, plywood, etc. Ideal finish for Hotels, Restaurants, Villas and all other prestigious interiors.



## Technical Data

Color	Selected range of Conmix Stucco Marbella standard
Finish	Smooth
Volume of Solids (Theoretical)	68 ± 2 %
Specific Gravity (ASTM D 1475)	1.50 ± 0.05
Theoretical coverage*	7 – 10 m <sup>2</sup> /kg
Surface Dry	1 – 2 hours
Dry to over coat	1 - 2 hours
Hard Dry	4 – 6 days
VOC	< 30 g/l

\*\* Indicates theoretical spreading rate. Theoretical Spreading Rate may also vary according to substrate condition or application method. The practical coverage is best established by a trial application on site and executed by your desired applicator.

\*\* The material cures physically by evaporation of water. Tested under typical laboratory conditions.



## Performance Features and Benefits

- Creates an elegant and antique finish
- High sheen and smooth finish
- Environment friendly
- Easy to apply and ready to use
- Safe, non-toxic, non-flammable and easy to clean with soap and water
- Fully respects people's health and environment



## Surface Preparation

- New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.
- Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water.
- Substrate should have sufficient strength to receive the paint. Any defects in the substrate like surface undulations, cracks, pin holes, excessive dampness etc., should be rectified/filled before starting painting.
- The performance of this coating is directly related to the quality of surface preparation.



### Method of Application

- Depending on the type and condition of the substrate, apply suitable primer/sealer prior to application. Over suitable masonry surface it is required to apply prime coat of ConDure Primer.
- Allow thorough drying of priming coat before further application.
- We are recommending to apply 1st coat of Basecoat prior to application of Conmix Stucco Marbella for colour shade adjusting. The Basecoat must be similar of colour shade as Conmix Stucco Marbella.
- Apply two coats of Conmix Stucco Marbella for smooth finish followed by two coats with desired design.
- The material can be applied using a fine blade spatula, building up a number of layers over a period of time.
- A gloss can be achieved by rubbing the Conmix Stucco Marbella with a trowel when wet or dry. Repeat the same process of application at least three to four times to obtain a very smooth, marble like finish.

Conmix technical service team will assist in these procedures upon request.

Note : It is highly recommended that this product is applied by a skilled and a professional painter.



### Recommended Paint System

- 1 x ConDure PVA Primer
- 1 x PinTura Matt Emulsion
- 2 x Conmix Stucco Marbell (For smooth finish)
- 2 x Conmix Stucco Marbell (For desired finish)



### Pack Size

5 KG & 25 KG



### Shelf Life

18 months from date of production, provided the product is stored properly in original unopened packing under proper storage conditions.



### Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Container must be kept tightly closed.



### Safety Information & Exposure Controls

Generally most of the water based paints are quite safe to handle with due precautions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Refer material safety data sheet as well.



### General Information

Stir well prior to use.

Keep the container tightly closed to prevent drying.



### Special Notes

Before painting the following aspect should be checked thoroughly:

- Moisture content of the wall (ideal condition - below 8%)
- pH value of the wall surface (ideal condition - below 11)

