


## COMBINATION WRENCHES

## STANDARD SERIES

## ▼ 40 METRIC AND INCH OGV® COMBINATION WRENCHES

▷ ISO 3318, DIN 3113, NF E 74-304

- 12-point OGV® ring angled at 15°.
- H: 6-point ring angled at 15°.
- Metric sizes from 3.2 to 32 mm.
- Inch sizes from 1/4" to 1 1/4".
- Satin chrome finish.



⊖	⊖	B	B'	C	C'	L	ΔΔ
A mm	A"	mm	mm	mm	mm	mm	g
40.4H		10,0	7,7	3,0	3,0	105	10
40.5H		14,2	9,6	3,6	5,0	113	14
40.5,5H		14,2	10,0	3,8	5,0	113	14
40.6	40.1/4	15,0	10,4	3,8	6,0	113	18
40.7		17,6	11,7	3,8	5,7	121	23
40.8	40.5/16	19,5	12,9	4,3	6,0	130	28
40.9	40.11/32	21,6	14,2	4,3	6,1	137	34
40.10	40.3/8	23,6	15,9	4,8	6,6	145	40
40.11	40.7/16	25,6	17,0	5,1	7,0	153	53
40.12		27,5	18,4	5,3	7,5	161	59
40.13	40.1/2	29,4	19,8	5,6	8,0	170	70
40.14	40.9/16	31,5	21,2	6,0	8,5	178	80
40.15		33,5	22,4	6,6	9,2	185	85
40.16	40.5/8	35,5	23,8	6,9	9,8	193	104

⊖	⊖	B	B'	C	C'	L	ΔΔ
A mm	A"	mm	mm	mm	mm	mm	g
40.17	40.11/16	37,5	25,0	7,0	10,3	200	120
40.18		39,5	26,4	7,4	10,9	208	136
40.19	40.3/4	41,8	29,4	7,6	11,3	216	160
40.20	40.13/16	44,0	29,4	8,0	11,6	224	172
40.21		46,0	30,7	8,1	11,9	233	200
40.22	40.7/8	48,0	32,0	8,2	12,3	248	212
40.23		50,0	33,4	8,4	12,6	258	251
40.24	40.15/16	52,0	34,7	8,5	12,9	268	270
40.25	40.1"	54,4	36,3	8,5	13,2	270	297
40.26		57,0	38,0	8,6	13,6	284	320
40.27	40.1 1/16	59,0	39,0	8,8	14,2	294	355
40.28	40.1 1/8	61,6	41,0	9,0	14,4	305	394
40.29		64,0	43,0	9,3	14,9	320	454
40.30		66,0	44,2	9,6	15,3	340	472
40.32	40.1 1/4	68,8	46,0	10,1	16,0	356	575