

ISORYL SCREWDRIVERS FOR SLOTTED HEADS

▼ AR FOR SLOTTED HEADS - MACHINED BLADES

- Shank machined for access into recesses.
- Polished chrome finish.

≡	e x A mm	T mm	Ø1 x L1 mm	Ø2 x L2 mm	L mm	ΔΔ g
AR.2X40	0,4 x 2,0	0,2	2,0 x 40	16,0 x 70	110	13,5
AR.2.5X50	0,4 x 2,5	0,2	2,5 x 50	16,0 x 70	120	15
AR.2.5X75	0,4 x 2,5	0,2	2,5 x 75	16,0 x 70	145	16
AR.3X75	0,5 x 3,0	0,3	3,0 x 75	16,0 x 70	145	17,5
AR.3.5X75	0,6 x 3,5	0,4	3,5 x 75	20,5 x 80	155	31
AR.3.5X100	0,8 x 4,0	0,4	3,5 x 100	20,5 x 80	180	33
AR.4X100	0,8 x 4,0	0,5	4,0 x 100	24,0 x 90	190	45
AR.4X150	0,8 x 4,0	0,5	4,0 x 150	24,0 x 90	240	50
AR.5.5X100	1,0 x 5,5	0,6	5,5 x 100	28,0 x 100	200	71
AR.5.5X150	1,0 x 5,5	0,6	5,5 x 150	28,0 x 100	250	80
AR.6.5X100	1,2 x 6,5	0,7	6,5 x 100	30,0 x 110	210	102
AR.6.5X150	1,2 x 6,5	0,7	6,5 x 150	30,0 x 110	260	114
AR.8X150	1,2 x 8,0	0,7	8,0 x 150	30,0 x 110	260	141

