

Frese frontali cilindriche a 2 taglienti in HSS-CO8% con attacco Weldon

HSS-CO8% two flutes end mills, Weldon shank / Fraises à rainurer HSS-CO8%, deux dents, queue Weldon

Fresas frontales HSS-CO8%, mango Weldon /Zweischneider Langlochfräser

DIN 327 D

Serie corta / Short serie / Série courte / Serie corta / Kurze Ausführung

Art. 24001
HSS-Co8%

Art. 24003
HSS-Co8%+TiAlN

24001 24003



Fresa per cave
Slot end mills

Ø	tol.	d	L	/	z	pcs	cod.	€ cad/each	cod.	€ cad/each
mm		mm	mm	mm						
2	e8	6	48	4	2	1	240010200		240030200	
2,5	e8	6	49	5	2	1	240010250		240030250	
3	e8	6	49	5	2	1	240010300		240030300	
3,5	h10	6	51	7	2	1	240010350		240030350	
4	e8	6	51	7	2	1	240010400		240030400	
4,5	h10	6	52	8	2	1	240010450		240030450	
5	e8	6	52	8	2	1	240010500		240030500	
5,5	h10	6	52	8	2	1	240010550		240030550	
6	e8	6	52	8	2	1	240010600		240030600	
6,5	h10	10	60	10	2	1	240010650		240030650	
7	e8	10	60	10	2	1	240010700		240030700	
7,5	h10	10	61	11	2	1	240010750		240030750	
8	e8	10	61	11	2	1	240010800		240030800	
8,5	h10	10	61	11	2	1	240010850		240030850	
9	h10	10	61	11	2	1	240010900		240030900	
9,5	h10	10	63	13	2	1	240010950		240030950	
10	e8	10	63	13	2	1	240011000		240031000	
11	h10	12	73	16	2	1	240011100		240031100	
12	e8	12	73	16	2	1	240011200		240031200	
13	h10	12	73	16	2	1	240011300		240031300	
14	e8	12	73	16	2	1	240011400		240031400	
15	h10	12	79	19	2	1	240011500		240031500	
16	e8	16	79	19	2	1	240011600		240031600	
18	e8	16	79	19	2	1	240011800		240031800	
20	e8	20	88	22	2	1	240012000		240032000	

DIN 844 L

Serie lunga / Long serie / Série longue / Serie larga / Lange Ausführung

Art. 24002
HSS-Co8%

Art. 24004
HSS-Co8%+TiAlN

24002 24004



Fresa per cave
Slot end mills

Ø	d	L	/	z	pcs	cod.	€ cad/each	cod.	€ cad/each
h10	mm	mm	mm						
3	6	56	12	2	1	240020300		240040300	
4	6	63	19	2	1	240020400		240040400	
5	6	68	24	2	1	240020500		240040500	
6	6	68	24	2	1	240020600		240040600	
8	10	88	38	2	1	240020800		240040800	
10	10	95	45	2	1	240021000		240041000	
12	12	110	53	2	1	240021200		240041200	
14	12	110	53	2	1	240021400		240041400	
16	16	123	63	2	1	240021600		240041600	
18	16	123	63	2	1	240021800		240041800	
20	20	141	75	2	1	240022000		240042000	

Confezione / Packaging



- Acciai e metalli con R<850 N/mm², ghisa con durezza HB30<200.
- Steel and metals with R<850 N/mm², cast iron with HB30<200.

Applicazioni / Applications

