



24001

HSS-CO 8% DIN 327 D



Ø		d	L	l	z	uds.	cód.
	tol.	mm	mm	mm			
2	e8	6	48	4	2	1	240010200
2,5	e8	6	49	5	2	1	240010250
3	e8	6	49	5	2	1	240010300
3,5	h10	6	51	7	2	1	240010350
4	e8	6	51	7	2	1	240010400
4,5	h10	6	52	8	2	1	240010450
5	e8	6	52	8	2	1	240010500
5,5	h10	6	52	8	2	1	240010550
6	e8	6	52	8	2	1	240010600
6,5	h10	10	60	10	2	1	240010650
7	e8	10	60	10	2	1	240010700
7,5	h10	10	61	11	2	1	240010750
8	e8	10	61	11	2	1	240010800
8,5	h10	10	61	11	2	1	240010850
9	h10	10	61	11	2	1	240010900
9,5	h10	10	63	13	2	1	240010950
10	e8	10	63	13	2	1	240011000
11	h10	12	73	16	2	1	240011100
12	e8	12	73	16	2	1	240011200
13	h10	12	73	16	2	1	240011300
14	e8	12	73	16	2	1	240011400
15	h10	12	79	19	2	1	240011500
16	e8	16	79	19	2	1	240011600
18	e8	16	79	19	2	1	240011800
20	e8	20	88	22	2	1	240012000

Fraises à rainurer



Applications



Acier



Métaux



Emulsion



Fonte
HB30<200



A sec

Acier et métaux avec $R < 850 \text{ N/mm}^2$, fonte avec HB30<200.