

**SUPPORT TUBE CONTACT M8 EN ETUI P/TORCHE MIG LG360**


**LG 360 G**



**Application\***

Application*	Ø	Short Arc STT®	Spray Arc	Puisé
MIG/MAG (80%Ar/20%CO <sub>2</sub> )	0,8 1,0 1,2	■ ■ ■	■ ■ ▲	■ ■ ■
Fil fourré (80%Ar/20%CO <sub>2</sub> )	1,2 1,4 1,6	■ ■ ■	■ ▲	■ ■ ■
Inox (98%Ar/2%CO <sub>2</sub> )	0,8 1,0 1,2	■ ■ ■	■ ■ ▲	■ ■ ▲
Aluminium (100%Ar)	1,0 1,2 1,6		▲ ▲ ▲	▲ ▲ ▲

**Buses**



Description	Ref. pièce	Ø	Qté /étui
Conique	KP10461-3	16mm	
Très conique	KP10461-8	12 mm	
Cylindrique	KP10460-3	20 mm	10pcs
Pour pointage	KP10463-3	20 mm	

**LG 360 G**  
LG360 G 3M  
LG360 G 4M  
LG360 G 5M

K10413-36-3M  
K10413-36-4M  
K10413-36-5M

**Caractéristiques techniques**

	Mélange gaz (M21)	100% CO <sub>2</sub>
Facteur de marche (10min 40C°)	335A 60%	350A 60%
Diamètres de fil	0,8-1,2mm	
Refroidissement	Air	min 12l/min

**Pièces d'usure**

M8	M6
Support tube contact M8	Support tube contact M6
KP10456-1	KP10455-2
10 pcs/étui	10 pcs/étui

Diffuseur gaz
KP10405-WT
10 pcs/étui