

STICK RANGE

	Product	Reference	Voltage (V)	Frequency (Hz)	Phase	Fuse Size (A) (slow)	No load voltage	Display	PFC	Current Range DC	Electrode diameter	Warranty (Years)	Weight (kg)	Rated Output	Protection Class
Inverter	Invertec® 150S	K12034-1	230	50 / 60	1	17	45			10-140	3,2	2	6,7	140A / 25,6V@25% 80A / 25,6V@100%	IP23 / F
	Invertec® 150S Pack	K12034-1-P													
	Invertec® 170S	K12035-1	230	50 / 60	1	23	45	•		10-160	4	2	7	160A / 26,4V@20% 80A / 24,0V@100%	IP23 / F
	Invertec® 170S Pack	K12035-1-P													
	Invertec® 160SX	K12050-1	115 / 230	50 / 60	1	16	48	•	•	5-160	4	3	9	160A / 24V@15% 100A / 26,4V@100%	IP23 / H
	Invertec® 165S	K14171-1	230	50 / 60	1	16	48			5-160 / 10-160	4	2	7	160A@20% / 160A@30% 100A@60% / 140A@60%	IP23
	Invertec® 165SX	K14170-1	230	50 / 60	1	16	48	•	•		4	2	7		IP23
	Invertec® V270 S 2V	K12022-3	230 / 400	50 / 60	3	35 / 20	48	•		5-270	5	2	13,5	270A / 30,8V@35% 200A / 28V@100%	IP23S / H
	Invertec® 270SX	K12040-1	400	50 / 60	3	20	45	•		5-270	5	3	22		IP23 / H
	Invertec® 400SX	K12042-1	400	50 / 60	3	30	45	•		5-400	6,3	3	36	400A / 36V@35% 300A / 32V@100%	IP23 / H
Conventional	LINC 405-S	K14002-2	230 / 400	50 / 60	3	63 / 40	78			15-400	6,3	3	126	400A / 36V@35% 240A / 29V@100%	IP23 / H
	LINC 405-SA	K14002-1						•							
	LINC 406	K14104-1	230 / 380 / 440	50 / 60	3	63 / 40 / 32	78	•		40-400	6,3	3	135	400A / 36V@35% 240A / 29V@100%	IP23 / H
	LINC 635-S	K14038-2	230 / 400	50 / 60	3	100 / 63	78			15-670	6,3	3	150	670A / 44V@35% 400A / 36V@100%	IP23 / H
	LINC 635-SA	K14038-1						•							
	HOT ROD 500S	K14089-1	380 / 415	50 / 60	3	63		•		50-625	6,3	3	203	600A/44V/35% 375A/35V/100%	IP23 / H

