

ABC DRY POWDER PORTABLE FIRE EXTINGUISHERS



CERTIFICATE NO:463
(Ref redbooklive.com)



FEATURES


- Mono-ammonium phosphate based dry chemical agent. Capable of fighting Class A, B, C and E fires.
- Kitemark approved ABC 85% & ABC 40% MAP based dry chemical agent for Class A, B & C Fires
- Kitemark/LPCB certified to BS EN3.
- Cylinders compliance to council directive 2014/68/EU (PED) is certified by BSI (2797).
- Certified by BSI under marine equipment directive, 2014/90/EU (MED)
- High quality polyester paint.
- Controlled discharge.
- Brass nickel plated head valve with simple squeeze operation.
- Unique gauge testing system.
- Unique color coded handle and base (optional).
- Rechargeable and easy to service.
- Choice of capacity from 1 to 12 kg.

***IDEAL USE:** Houses, office, buildings, warehouses, farms, wood working area etc.

***NOTE:** Not recommended for use on expensive and delicate equipment like computers, etc.

SPECIFICATION

Model Number	NP1	NP2	NP3	NP4	NP6	NP9	NP12
Extinguisher Capacity	1 kg	2 kg	3 kg	4 kg	6 kg	9 kg	12 kg
Propellant	95% Nitrogen + 5% Helium						
Fire Rating	8A 34B	13A 70B	21A 89B	21A 113B	34A 183B	43A 233B	55A 233B
Working Pressure	14 bar	14 bar	14 bar	15 bar	15 bar	15 bar	15 bar
Maximum Operating Pressure	18.5 bar @ 60°C						
Test Pressure	30 bar						
Total Weight	2.0 kg	3.7 kg	5.8 kg	7.5 kg	10 kg	14 kg	17.8 kg
Range of Discharge	4-5 m	5-7 m	6-7 m	7-8 m	6-8 m	6-8 m	6-8 m
Duration of Discharge	7-9 sec.	10-12 sec.	11-12 sec.	13-15 sec.	18-20 sec.	22-24 sec.	28-30 sec.
Hose Length with Nozzle	N/A	N/A	395 mm	457 mm	534 mm	534 mm	617 mm
Operating Temperature	-20°C to +60°C						
Cylinder Material	CRCA Steel						
Height x Diameter (mm)	365 x 75	385 x 110	420 x 132	408 x 150	520 x 150	515 x 185	620 x 185



1. Valve/Extn. Lever
2. Safety Pin with Chain
3. Valve Handle
4. Pressure Gauge
5. Discharge Hose
6. Syphon Tube
7. Hose Holder
8. Discharge Nozzle
9. PVC Base

