



WTT2 TORCHES


Simple and reliable, this range is adapted to the most common applications.




Extra-flexible high performance cable.



Easy pivoting handle (for EB handles).



Standardised wear parts.



Handle, made with high temperature silicon rubber.



Air cooling

MODEL		WTT2 9		WTT2 17		WTT2 26			
Duty cycle at 40 °C		60%	80 A	100 A	130 A				
		35%	110 A	135 A	180 A				
Original equipment		back cap	Long						
		nozzle	∅ 9.6 mm	∅ 9.6 mm	∅ 12.8 mm				
		electrode	∅ 1.6 mm	∅ 2.0 mm	∅ 2.4 mm				
Length		4 m	8 m	4 m	8 m	4 m	8 m		
Handle	RL	Connection	S	W000278878	W000278923	W000278883	W000278918	W000278888	W000278914
			C5B	W000278879	W000278922	W000278884	W000278917	W000278890	W000278913
	EB		S	W000278877	W000278929	W000278881	W000278920	W000278886	W000278916
			C5B	W000278875	-	W000278882	W000278919	W000278887	W000278915
	V		V (Conn. 9 mm)	W000278876	-	W000278880	-	-	-
			V (Conn. 13 mm)	-	-	W10529-17-4V	-	W000278885	-
	EB-FLEX		S / C5B	W000382781	-	W000382782	W000382783	W000382784	W000382785

Connections



C5B



S

Connector:

Shaped cable output for a better robustness.



Air cooling



Water cooling

Water cooling

MODEL		WTT2 20 W		WTT2 18 W			
Duty cycle at 40 °C		100%	200 A	320 A			
		60%	250 A	350 A			
Original equipment		back cap	Long				
		nozzle	∅ 12.8 mm		∅ 16 mm		
		electrode	∅ 2.4 mm		∅ 3.2 mm		
Length		4 m	8 m	4 m	8 m		
Handle	RL	Connection	S	W000278893	W000278906	W000278897	W000278900
			C5B	W000278894	W000278905	W000278898	W000278899
	EB		S	W000278891	W000278911	W000278895	W000278902
			C5B	W000278892	W000278909	W000278896	W000278901
	EB-FLEX		S / C5B	W000382786	W000382787	W000382788	W000382789

Handle



RL



EB



V



EB-FLEX