

Inox A2

62 429


DIN 7504 M - (similar ISO 15481)

VIS AUTOPERCEUSES TETE CYLINDRIQUE PHILLIPS

PHILLIPS PAN HEAD SELF DRILLING SCREWS

BOHRSCHRAUBEN MIT LINSENKOPF UND KREUZSCHLITZ H

TORNILLOS AUTOTALADRANTES CABEZA CILINDRICA PHILLIPS



d	3,5 (6)	3,9 (7)	4,2 (8)	4,8 (10)
d2	6,9	7,5	8,2	9,5
k	2,6	2,8	3,05	3,55
⊕	2	2	2	2
Capacité de perçage	2	2	3	4

d x L	Code	Cond.	kg/100	d x L	Code	Cond.	kg/100
3,5X9,5	624293,5X9,5	200	0,104	4,2X16	624294,2X16	200	0,170
3,5X13	624293,5X13	200	0,119	4,2X19	624294,2X19	200	0,220
3,5X16	624293,5X16	200	0,132	4,2X25	624294,2X25	200	0,257
3,5X19	624293,5X19	200	0,144	4,2X32	624294,2X32	200	0,306
3,5X25	624293,5X25	200	0,170	4,2X38	624294,2X38	200	0,339
3,5X28	624293,5X28	200	0,183	4,8X16	624294,8X16	200	0,310
3,5X32	624293,5X32	200	0,200	4,8X19	624294,8X19	200	0,335
3,5X38	624293,5X38	200	0,225	4,8X25	624294,8X25	200	0,384
3,9X13	624293,9X13	200	0,136	4,8X32	624294,8X32	200	0,391
3,9X16	624293,9X16	200	0,160	4,8X38	624294,8X38	200	0,491
3,9X19	624293,9X19	200	0,178	4,8X45	624294,8X45	200	0,548
3,9X22	624293,9X22	200	0,200	4,8X50	624294,8X50	200	0,589
3,9X25	624293,9X25	200	0,208	4,8X60	624294,8X60	200	0,671
3,9X32	624293,9X32	200	0,235	4,8X70	624294,8X70	200	0,754
3,9X38	624293,9X38	200	0,267	4,8X80	624294,8X80	200	0,836
4,2X13	624294,2X13	200	0,183				



Perce seulement l'aluminium / Drills only aluminium
 Informations d'utilisation voir page 43 / Using instructions : see page 43