

Tubes Noires Sans Soudure API 5L / ASTM A106 Gr.B Schédule 80

Diametre nominal	ø Ext.	Désignations			Epaisseur		Poids		ø Int.	
					INCH	MM	LBS/FOOT	KG/METER	INCH	MM
INCH MM	INCH MM	ASME			INCH	MM	LBS/FOOT	KG/METER	INCH	MM
1/8 6	0.405 10.3	10	10S	0.049	1.24	0.19	0.28	0.307	7.82	
		STD 40	40S	0.068	1.73	0.24	0.37	0.269	6.84	
		XS 80	80S	0.095	2.41	0.31	0.47	0.215	5.84	
1/4 8	0.540 13.7	10	10S	0.065	1.65	0.33	0.49	0.410	10.40	
		STD 40	40S	0.088	2.24	0.43	0.63	0.364	9.22	
		XS 80	80S	0.119	3.02	0.54	0.80	0.302	7.66	
3/8 10	0.675 17.1	10	10S	0.065	1.65	0.42	0.63	0.545	13.80	
		STD 40	40S	0.091	2.31	0.57	0.84	0.493	12.48	
		XS 80	80S	0.126	3.20	0.74	1.10	0.423	10.70	
1/2 15	0.840 21.3	5	5S	0.065	1.65	0.54	0.80	0.710	18.00	
		10	10S	0.083	2.11	0.67	1.00	0.674	17.08	
		STD 40	40S	0.109	2.77	0.85	1.27	0.622	15.76	
		XS 80	80S	0.147	3.73	1.09	1.62	0.546	13.84	
		120		0.188	4.78	1.31	1.95	0.464	11.74	
		XX		0.294	7.47	1.72	2.55	0.252	6.36	
3/4 20	1.050 26.7	5	5S	0.065	1.65	0.69	1.03	0.920	23.40	
		10	10S	0.083	2.11	0.86	1.28	0.884	22.48	
		STD 40	40S	0.113	2.87	1.13	1.69	0.824	20.96	
		XS 80	80S	0.154	3.91	1.48	2.20	0.742	18.88	
		160		0.219	5.56	1.95	2.90	0.612	15.58	
		XX		0.308	7.82	2.44	3.64	0.434	11.06	
1 25	1.315 33.4	5	5S	0.065	1.65	0.87	1.29	1.185	30.10	
		10	10S	0.109	2.77	1.41	2.09	1.097	27.86	
		STD 40	40S	0.133	3.38	1.68	2.50	1.049	26.64	
		XS 80	80S	0.179	4.55	2.17	3.24	0.957	24.30	
		160		0.250	6.35	2.85	4.24	0.815	20.70	
		XX		0.358	9.09	3.66	5.45	0.599	15.22	
1/1-4 32	1.660 42.2	5	5S	0.065	1.65	1.11	1.65	1.530	38.90	
		10	10S	0.109	2.77	1.81	2.69	1.442	36.66	
		STD 40	40S	0.140	3.56	2.27	3.39	1.380	35.08	
		XS 80	80S	0.191	4.85	3.00	4.47	1.278	32.50	
		160		0.250	6.35	3.77	5.61	1.160	29.50	
		XX		0.382	9.70	5.22	7.77	0.896	22.80	
1/1-2 40	1.900 48.3	5	5S	0.065	1.65	1.28	1.90	1.770	45.00	
		10	10S	0.109	2.77	2.09	3.11	1.682	42.76	
		STD 40	40S	0.145	3.68	2.72	4.05	1.610	40.94	
		XS 80	80S	0.200	5.08	3.63	5.41	1.500	38.14	
		160		0.281	7.14	4.86	7.25	1.338	34.02	
		XX		0.400	10.15	6.41	9.55	1.100	28.00	
2 50	2.375 60.3	5	5S	0.065	1.65	1.61	2.39	2.245	57.00	
		10	10S	0.109	2.77	2.64	3.93	2.157	54.76	
		STD 40	40S	0.154	3.91	3.66	5.44	2.067	52.48	
		XS 80	80S	0.218	5.54	5.03	7.48	1.939	49.22	
		160		0.344	8.74	7.47	11.11	1.687	42.82	
		XX		0.436	11.07	9.04	13.44	1.503	38.16	
2/1-2 65	2.875 73.0	5	5S	0.083	2.11	2.48	3.69	2.709	68.78	
		10	10S	0.120	3.05	3.53	5.26	2.635	66.90	
		STD 40	40S	0.203	5.16	5.80	8.63	2.469	62.68	
		XS 80	80S	0.276	7.01	7.67	11.41	2.323	58.98	
		160		0.375	9.53	10.02	14.92	2.125	53.94	
		XX		0.552	14.02	13.71	20.39	1.771	44.96	
3 80	3.500 88.9	5	5S	0.083	2.11	3.03	4.52	3.334	84.68	
		10	10S	0.120	3.05	4.34	6.46	3.260	82.80	
		STD 40	40S	0.216	5.49	7.58	11.29	3.068	77.92	
		XS 80	80S	0.300	7.62	10.26	15.27	2.900	73.66	
		160		0.438	11.13	14.34	21.35	2.624	66.64	
		XX		0.600	15.24	18.60	27.68	2.300	58.42	
3/1-2 90	4.000 101.6	5	5S	0.083	2.11	3.48	5.18	3.834	97.38	
		10	10S	0.120	3.05	4.98	7.41	3.760	95.50	
		STD 40	40S	0.226	5.74	9.12	13.57	3.548	90.12	
		XS 80	80S	0.318	8.08	12.52	18.64	3.364	85.44	
		160		0.636	16.15	22.87	34.03	2.728	69.30	
		XX								
4 100	4.500 114.3	5	5S	0.083	2.11	3.92	5.84	4.334	110.08	
		10	10S	0.120	3.05	5.62	8.37	4.260	108.20	
				0.156	3.96	7.24	10.78	4.188	106.38	
				0.188	4.78	8.67	12.91	4.124	104.74	
		STD 40	40S	0.237	6.02	10.80	16.08	4.026	102.26	
		XS 80	80S	0.337	8.56	15.00	22.32	3.826	97.18	
		120		0.438	11.13	19.02	28.32	3.624	92.04	
		160		0.531	13.49	22.53	33.54	3.438	87.32	
		XX		0.674	17.12	27.57	41.03	3.152	80.06	
				0.710	18.03	32.56	48.45	3.580	90.94	

Diametre nominal	ø Ext.	Désignations			Epaisseur		Poids		ø Int.	
					INCH	MM	LBS/FOOT	KG/METER	INCH	MM
INCH MM	INCH MM	ASME			INCH	MM	LBS/FOOT	KG/METER	INCH	MM
5 125	5.563 141.3	5	5S	0.109	2.77	6.36	9.46	5.345	135.76	
		10	10S	0.134	3.40	7.78	11.56	5.295	134.50	
		STD 40	40S	0.258	6.55	14.63	21.77	5.047	128.20	
		XS 80	80S	0.375	9.53	20.80	30.97	4.813	122.24	
		120		0.500	12.70	27.06	40.28	4.563	115.90	
		160		0.625	15.88	32.99	49.12	4.313	109.54	
6 150	6.625 168.3	5	5S	0.109	2.77	7.59	11.31	6.407	162.76	
		10	10S	0.134	3.40	9.30	13.83	6.357	161.50	
				0.188	4.78	12.94	19.28	6.249	158.74	
		STD 40	40S	0.280	7.11	18.99	28.26	6.065	154.08	
		XS 80	80S	0.432	10.97	28.60	42.56	5.761	146.36	
		120		0.562	14.27	36.43	54.21	5.501	139.76	
7 175	7.625 193.7	5	5S	0.109	2.77	9.92	14.78	8.407	213.56	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58	42.55	7.981	202.74	
		60		0.406	10.31	35.67	53.09	7.813	198.48	
8 200	8.625 219.1	5	5S	0.109	2.77	13.41	19.97	8.329	211.58	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58	42.55	7.981	202.74	
		60		0.406	10.31	35.67	53.09	7.813	198.48	
9 225	9.625 244.5	5	5S	0.109	2.77	15.09	22.27	10.020	254.46	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58	42.55	7.981	202.74	
		60		0.406	10.31	35.67	53.09	7.813	198.48	
10 250	10.750 273.0	5	5S	0.109	2.77	15.09	22.27	10.020	254.46	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58	42.55	7.981	202.74	
		60		0.406	10.31	35.67	53.09	7.813	198.48	
11 275	11.750 298.5	5	5S	0.109	2.77	15.09	22.27	10.020	254.46	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58	42.55	7.981	202.74	
		60		0.406	10.31	35.67	53.09	7.813	198.48	
12 300	12.750 323.8	5	5S	0.109	2.77	15.09	22.27	10.020	254.46	
		10	10S	0.148	3.76	13.41	19.97	8.329	211.58	
		20		0.250	6.35	22.38	33.32	8.125	206.40	
		30		0.277	7.04	24.72	36.82	8.071	205.02	
		STD 40	40S	0.322	8.18	28.58				