HHEV2107



EV CHARGER

HHEV2107HM11KT24G

SPECIFICATION		
Power Input	Input Wiring Scheme	3P+N+PE
	Rated Voltage	400VAC±10%
	Rated Current	16A
	Grid Frequency	50 / 60 Hz
Power Output	Output Voltage	400VAC±10%
	max. Current	16A
	Rated Power	11kW
User Interface	Charge Connector	Type 2 Plug
	Cable Length	5m
	LED Indicator	Green/Blue/Red/Yellow
	LCD Display	4.3” Touch Color Screen
	RFID Reader	RFID Card Reader
	Start Mode	Plug & Charge/RFID Card/APP
Communication	Backend	**Bluetooth**/Ethernet/WiFi | Optional: 4G
	Charging protocol	OCPP-1.6J
Safety and Certification	Energy Meter	Embedded Meter
	Residual Current Device	Type A+DC 6mA
	Ingress Protection	IP54
	Impact Protection	IK10
	Cooling method	Natural Cooling
	Electrical Protection	Over/Under Voltage Protection,Over Current Protection, Short Circuit Protection, Over/Under Temperature Protection,Lightning Protection, Ground Protection
	Certification	TUV CB&CE
	Certification and Conformity	IEC61851-1.IEC62196-1
Environment	Mounting	Wall-mount/Pole-mount
	Storage Temperature	-40ºC- +85ºC
	Operating Temperature	-35ºC- +**55ºC**
	Max. Operating Humidity	95%, Non-condensing
	Max. Operating Altitude	2000m
Mechanical	Product Dimension	360mm*248mm*97mm(W*D*H)